

# XB9 5 joule xenon beacon range

Ex d, weatherproof



## Overview

These compact and lightweight beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The beacon housing, including the flamepaths, is manufactured completely from a UV stable glass reinforced polyester which is ideally suited for use offshore and onshore.

Stainless steel screws and mounting bracket are incorporated ensuring a totally corrosion free unit.

Units can be painted to customer specification and supplied with identification labels.

## Features

- Zone 1 and Zone 2 use
- Ex d IIC T5/T6
- ATEX approved, Ex II 2G
- IECEx certified Gb
- TR CU certified
- IP66 and IP67
- Certified temperature -55°C to +55°C
- Corrosion Free GRP
- Various lens colours
- Lens guard fitted as standard
- Optional gland plus cable tail
- Stainless steel mounting bracket & screws
- Replaceable tube



## Certifications

**ATEX Ex d** Cert. no. Baseefa BAS00ATEX2031  
 Certified to: EN60079-0, EN60079-1  
 Ex II 2G, Ex d IIC T5/T6 Gb

**IECEX Ex d** Cert. no. IECEX BAS 10.0113  
 Certified to: IEC60079-0, IEC60079-1  
 Ex d IIC T5/T6 Gb

**TR CU Ex d** 1Ex d IIC T5/T6 Gb

## Specifications

<b>Material</b>	Body & cover: glass reinforced polyester (GRP) Lens: glass Cover screws & bracket: stainless steel 316
<b>Finish</b>	Natural black or painted to customer specification
<b>Weight</b>	1.6kg
<b>Certified temp</b>	-55°C to +40°C (T6). -55°C to +55°C (T5)
<b>Ingress protection</b>	IP66 & IP67
<b>Fire retardancy</b>	GRP is fire retardant to IEC 60695-11-10
<b>Terminals</b>	3 x 2.5mm <sup>2</sup>
<b>Mounting</b>	Wall mounted via bracket
<b>Entries</b>	1 x M20 or PG 13.5
<b>Optional</b>	1 x 3m cable tail and gland
<b>Tube life</b>	>1x10 <sup>6</sup> flashes

## Electrical ratings:

Voltage	d.c				a.c.	
	12	24	48	60	110	240/254
Tube energy (J)	5	5	5	5	5	5
Current (A)	0.65	0.35	0.18	0.13	0.08	0.06/0.057
Effective intensity (Cd)	29	29	29	29	29	29
Peak intensity (Cd)	22213	22213	22213	22213	22213	22213
Power consumption (W)	8	9	9	8	9	15

Note: The above figures (Cd) are for a clear lens @ 1Hz flash rate

## Multiplying factor for coloured lenses:

Red	Blue	Amber	Green	Yellow
0.15	0.12	0.51	0.49	0.86

The photometric data has been verified by BSI. A report is available if required

## Ordering requirements

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box

Model	Certification	Voltage	Flashrate	Lens	Lens guard	Tag/duty	Entries/cable tail	Finish																																																				
<b>XB9</b>																																																												
	<table border="1"> <thead> <tr> <th>Certification</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Uncertified</td> <td>W</td> </tr> <tr> <td>ATEX</td> <td>D</td> </tr> <tr> <td>IECEX</td> <td>J</td> </tr> <tr> <td>TR CU</td> <td>G</td> </tr> </tbody> </table>	Certification	Code	Uncertified	W	ATEX	D	IECEX	J	TR CU	G		<table border="1"> <thead> <tr> <th>Flash rate</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>60 / min</td> <td>06</td> </tr> </tbody> </table> <p>Other flash rates available on request, please specify</p>	Flash rate	Code	60 / min	06		<table border="1"> <thead> <tr> <th>Guard</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Yes</td> <td>Y</td> </tr> </tbody> </table>	Guard	Code	Yes	Y		<table border="1"> <thead> <tr> <th>Entries</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>1 x M20</td> <td>1B</td> </tr> <tr> <td>1 x PG 13.5</td> <td>1P</td> </tr> <tr> <td>Cable &amp; tail 3m cable</td> <td>CB</td> </tr> </tbody> </table>	Entries	Code	1 x M20	1B	1 x PG 13.5	1P	Cable & tail 3m cable	CB																											
Certification	Code																																																											
Uncertified	W																																																											
ATEX	D																																																											
IECEX	J																																																											
TR CU	G																																																											
Flash rate	Code																																																											
60 / min	06																																																											
Guard	Code																																																											
Yes	Y																																																											
Entries	Code																																																											
1 x M20	1B																																																											
1 x PG 13.5	1P																																																											
Cable & tail 3m cable	CB																																																											
		<table border="1"> <thead> <tr> <th>Voltage</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>12Vdc</td> <td>012</td> </tr> <tr> <td>24Vdc</td> <td>024</td> </tr> <tr> <td>48Vdc</td> <td>048</td> </tr> <tr> <td>60Vdc</td> <td>060</td> </tr> <tr> <td>110Vac</td> <td>110</td> </tr> <tr> <td>240Vac</td> <td>240</td> </tr> <tr> <td>254Vac</td> <td>254</td> </tr> </tbody> </table>	Voltage	Code	12Vdc	012	24Vdc	024	48Vdc	048	60Vdc	060	110Vac	110	240Vac	240	254Vac	254		<table border="1"> <thead> <tr> <th>Colour</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Green</td> <td>G</td> </tr> <tr> <td>Amber</td> <td>A</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Clear</td> <td>C</td> </tr> </tbody> </table>	Colour	Code	Red	R	Blue	B	Green	G	Amber	A	Yellow	Y	Clear	C		<table border="1"> <thead> <tr> <th>Label</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>N</td> </tr> <tr> <td>Yes</td> <td>Y*</td> </tr> </tbody> </table> <p>*Please specify</p>	Label	Code	None	N	Yes	Y*		<table border="1"> <thead> <tr> <th>Finish</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Natural black</td> <td>N</td> </tr> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Grey</td> <td>G</td> </tr> <tr> <td>White</td> <td>W</td> </tr> <tr> <td>Special</td> <td>S*</td> </tr> </tbody> </table> <p>*Please specify</p>	Finish	Code	Natural black	N	Red	R	Blue	B	Yellow	Y	Grey	G	White	W	Special	S*
Voltage	Code																																																											
12Vdc	012																																																											
24Vdc	024																																																											
48Vdc	048																																																											
60Vdc	060																																																											
110Vac	110																																																											
240Vac	240																																																											
254Vac	254																																																											
Colour	Code																																																											
Red	R																																																											
Blue	B																																																											
Green	G																																																											
Amber	A																																																											
Yellow	Y																																																											
Clear	C																																																											
Label	Code																																																											
None	N																																																											
Yes	Y*																																																											
Finish	Code																																																											
Natural black	N																																																											
Red	R																																																											
Blue	B																																																											
Yellow	Y																																																											
Grey	G																																																											
White	W																																																											
Special	S*																																																											

## General arrangement drawing (all dimensions in mm)

